

TYPE:DG1450 BARRIER TERMINAL BLOCKS

THE VALUABLE CHOICE WITH QUALITY AND PRICE

最优的性能价格比

ADVANTAGE

- The insulation part is made from imported PBT with excellent fire retardance, And the highest temperature can reach to 140 degrees when in use.
- The current carrier is made of high-qualified copper with low contact resistance and excellent electrical conductivity
- The characteristics are accordance with IEC60998 and UL1059 standards
- The screw is made of high-qualified steel with excellent mechanical properties, and its salt spray test can reach to more than 48 hours.

产品的优点

- 绝缘件采用进口PBT材料，阻燃性好，最高电气保证使用温度140°C；
- 载流体采用优质铜材，接触电阻低，导电性能好；
- 产品性能符合IEC60998和UL1059标准要求；
- 螺钉采用优质钢材,机械性能好，盐雾试验达到48小时以上；



CE RoHS REACH

认证	CE	
电气性能		
参考标准	UL	IEC
额定电压	600V	800V
额定电流	45A	45A
使用线径	22-8AWG	10.0mm ²
耐电压	AC3500V/1Min	
机械性能		
温度范围	-40°C~+140°C	
剥线长度	8.5-9.5mm	
尺寸		
间距	14.5mm(.571")	
极数	2P-14P	
材质及电镀		
塑件	PBT+20%GF	
焊脚	Brass,Tin plated	

